

Lecture 18: Linking

Philipp Koehn

October 18, 2021

601.229 Computer Systems Fundamentals



Hello World

```
#include <stdlib.h>
#include <stdio.h>

int main(void) {
    printf("Hello world!\n");
    return EXIT_SUCCESS;
}
```

Compilation

- ▶ Compile

```
$ gcc -Og hello-world.c
```


- ▶ Resulting program

```
$ ls -l a.out
```

```
-rwxr-xr-x. 1 phi users 8512 Nov 16 03:57 a.out
```

- ▶ That's pretty small!

Dynamic Linking



Static Linking

- ▶ Compile with `--static`
- ▶ Results in very large file
- ▶ Includes the entire library!

Benefits of Dynamic Linking

- ▶ Makes code smaller
 - ▶ needs less disk space
 - ▶ needs less RAM
- ▶ Library is not part of the compiled program
 - ⇒ when it gets updated, no need to recompile

Example: Code in 2 Files

main.c

```
int sum(int *a, int n);

int array[2] = {1, 2};

int main() {
    int val = sum(array, 2);
    return val;
}
```


sum.c

```
int sum(int *a, int n) {
    int i, s = 0;
    for(i = 0; i<n; i++) {
        s += a[i];
    }
    return s;
}
```

Compile and Run

```
$ gcc -Og -o prog main.c sum.c
$ ./prog
$ echo $?
3
```


Static Linking



Static Linking

- ▶ Symbol resolution
 - ▶ object files define and reference symbols (functions, global variables, static variables)
 - ▶ need to connect symbol to exactly one definition

Static Linking

- ▶ Symbol resolution
 - ▶ object files define and reference symbols (functions, global variables, static variables)
 - ▶ need to connect symbol to exactly one definition
- ▶ Relocation
 - ▶ assemblers generate object files that starts at address 0
 - ▶ when combining multiple object files, code must be shifted
 - ▶ all reference to memory addresses must be adjusted
 - ▶ assembler stores meta information in object file
 - ▶ linker is guided by relocation entries

Object Files

- ▶ Relocatable object file
 - ▶ binary code
 - ▶ meta information that allows symbol resolution and relocation
- ▶ Executable object file
 - ▶ binary code
 - ▶ can be copied into memory and executed
- ▶ Shared object file
 - ▶ binary code
 - ▶ can be loaded into memory
 - ▶ can be linked dynamically

Relocatable Object Files

- ▶ Executable and Linkable Format (ELF)
 - ▶ header
 - ▶ sections with different type of data
 - ▶ section header table

ELF header
.text
.rodata
.data
.bss
.symtab
.rel.text
.re.data
.debug
.line
.strtab
Section header table

Sections

- .text** machine code of compiled program
- .rodata** read-only data (e.g., strings in printf statements)
- .data** initialized global and static C variables
- .bss** uninitialized global and static C variables
- .symtab** symbol table
- .rel.text** list of locations in .text section (machine code)
to be modified when object is relocated
- .rel.data** same for .data
- .debug** debugging symbol table
(only compiled with -g)
- .line** mapping between line number and machine code
(only compiled with -g)
- .strtab** string table for .symtab and .debug

Symbols

- ▶ Global symbols that can be used by other objects
- ▶ Global symbols of other objects (not defined here)
- ▶ Local symbols only used in object defined with "static" attribute
- ▶ Note: non-static local variable are not exposed

ELF Symbol Table Entry

Name	Pointer to string of symbol name
Type	Function or data type
Binding	Indicates local or global
Section	Index of which section it belongs to
Value	Section offset
Size	Size in bytes

Example

```
$ readelf -a main.o
```

```
Section Headers:
```

```
[ 1] .text  
[ 3] .data
```

Num:	Value	Size	Type	Bind	Vis	Ndx	Name
8:	0000000000000000	24	FUNC	GLOBAL	DEFAULT	1	main
9:	0000000000000000	8	OBJECT	GLOBAL	DEFAULT	3	array
10:	0000000000000000	0	NOTYPE	GLOBAL	DEFAULT	UND	sum

- ▶ main is a function (FUNC) in section .text (1)
- ▶ array is an object (OBJECT) in section .data (3)
- ▶ sum is undefined (UND)

Symbol Resolution

- ▶ Linker must resolve all symbols to connect references to addresses
- ▶ Local symbols are contained to their object, each has a unique name
- ▶ Symbols in an object file may be undefined (listed as UND in symbol table)
⇒ these must be defined in other objects
- ▶ If not found, linker complains:

```
$ gcc -Og main.c  
/tmp/ccZzl3Pp.o: In function `main':  
main.c:(.text+0xf): undefined reference to `sum'  
collect2: error: ld returned 1 exit status
```

Static Libraries

- ▶ Goal: link various standard functions statically
→ binary without dependency
- ▶ Plan A
 - ▶ put everything into big libc.o
 - ▶ link it to the application object file
 - ▶ ... but that adds too big of a file
- ▶ Plan B
 - ▶ have separate object files printf.o, scanf.o, ...
 - ▶ link only the ones that are needed
 - ▶ ... but that requires a lot of tedious bookkeeping by programmer

Static Libraries

- ▶ Solution: archives
- ▶ Combine object files `printf.o`, `scanf.o`, ... into archive `libc.a`
- ▶ Let linker pick out the ones that are needed
\$ `gcc main.c /usr/lib/libc.a`

Static Libraries

- ▶ Solution: archives
- ▶ Combine object files `printf.o`, `scanf.o`, ... into archive `libc.a`
- ▶ Let linker pick out the ones that are needed
`$ gcc main.c /usr/lib/libc.a`
- ▶ You can build your own libraries
`$ ar rcs libmy.a my1.o my2.o my3.o`

Relocation

- ▶ Multiple object files
- ▶ Merge all sections, e.g., all .data sections together
- ▶ Assign run time memory addresses for each symbol
- ▶ Modify each symbol reference
- ▶ This is aided by relocation entries

Relocation Entry

Offset	Offset of reference within object
Type	Relocation type
Symbol	Symbol table index
Added	Constant part of relocation expression

Type may be

- ▶ absolute 32 bit address, or
- ▶ address relative to program counter

Zoom poll!

Consider the following code:

```
1: extern int a; // defined elsewhere
2:
3: void f(int b) {
4:     a++;
5:     b++;
6:     printf("%d %d", a, b);
7: }
```

- A. 4 only
- B. 5 only
- C. 6 only
- D. 4 and 6
- E. 4, 5, and 6

For which source lines are relocation entries needed to resolve the addresses of code or data?

Relocating Symbol Addresses

▶ main.o

```
0: 48 83 ec 08          sub    $0x8,%rsp
4: be 02 00 00 00      mov    $0x2,%esi
9: bf 00 00 00 00      mov    $0x0,%edi
e: e8 00 00 00 00      callq 13 <main+0x13>
13: 48 83 c4 08         add    $0x8,%rsp
17: c3                  retq
```

▶ Relocation entries

- ▶ a: R_X86_64_32 array
- ▶ f: R_X86_64_PC32 sum-0x4
- ▶ At line 9: reference to array
- ▶ At line e: reference to sum function (undefined in object)

```
0000000000000000 <sum>:
  0: b8 00 00 00 00      mov     $0x0,%eax
  5: ba 00 00 00 00      mov     $0x0,%edx
  a: eb 09              jmp     15 <sum+0x15>
  c: 48 63 ca          movslq  %edx,%rcx
  f: 03 04 8f          add     (%rdi,%rcx,4),%eax
12: 83 c2 01          add     $0x1,%edx
15: 39 f2              cmp     %esi,%edx
17: 7c f3              jl      c <sum+0xc>
19: f3 c3              repz   retq
```

main.o + sum.o → prog

```
00000000004004f6 <main>:
 4004f6: 48 83 ec 08          sub    $0x8,%rsp
 4004fa: be 02 00 00 00      mov    $0x2,%esi
 4004ff: bf 30 10 60 00      mov    $0x601030,%edi
 400504: e8 05 00 00 00      callq 40050e <sum>
 400509: 48 83 c4 08          add    $0x8,%rsp
 40050d: c3                  retq

000000000040050e <sum>:
 40050e: b8 00 00 00 00      mov    $0x0,%eax
 400513: ba 00 00 00 00      mov    $0x0,%edx
 400518: eb 09              jmp    400523 <sum+0x15>
 40051a: 48 63 ca          movslq %edx,%rcx
 40051d: 03 04 8f          add    (%rdi,%rcx,4),%eax
 400520: 83 c2 01          add    $0x1,%edx
 400523: 39 f2              cmp    %esi,%edx
 400525: 7c f3              jl     40051a <sum+0xc>
 400527: f3 c3              repz  retq
 400529: 0f 1f 80 00 00 00 00  nopl  0x0(%rax)
```

Loading Executable Object Files

