

Lecture 33: I/O multiplexing

Brennon Brimhall

21 July 2025

Example code

Example code for today is on course website in $\verb"iomux.zip"$





Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd);
  close(client_fd);
}
```



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL); // Indefinite wait
  chat_with_client(client_fd);
  close(client_fd);
}
```



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd); // Indefinite wait
  close(client_fd);
}
```



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd);
  close(client_fd);
}
```

The server is not responsive while



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd);
  close(client_fd);
}
```

The server is not responsive while

1. Waiting for client connection to arrive



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd);
  close(client_fd);
}
```

The server is not responsive while

- 1. Waiting for client connection to arrive
- 2. Waiting to receive data from client



Server main loop:

```
int server_fd = open_listenfd(port);
while (1) {
  int client_fd =
    Accept(server_fd, NULL, NULL);
  chat_with_client(client_fd);
  close(client_fd);
}
```

The server is not responsive while

- 1. Waiting for client connection to arrive
- 2. Waiting to receive data from client
- 3. Waiting to send data to client (sometimes required by TCP protocol)



• Operations such as accept, read, and write can block



- Operations such as accept, read, and write can block
- "Blocking" means that the OS kernel suspends the calling thread until the operation has completed



- Operations such as accept, read, and write can block
- "Blocking" means that the OS kernel suspends the calling thread until the operation has completed
- E.g., when calling accept, the calling thread is blocked until a request for a new client connection



- Operations such as accept, read, and write can block
- "Blocking" means that the OS kernel suspends the calling thread until the operation has completed
- E.g., when calling accept, the calling thread is blocked until a request for a new client connection
- Problem: while a thread is blocked, it can't do anything else



- Operations such as accept, read, and write can block
- "Blocking" means that the OS kernel suspends the calling thread until the operation has completed
- E.g., when calling accept, the calling thread is blocked until a request for a new client connection
- Problem: while a thread is blocked, it can't do anything else
- So, there is no way to support multiple simultaneous clients, and have the server be responsive, using a single thread



- Operations such as accept, read, and write can block
- "Blocking" means that the OS kernel suspends the calling thread until the operation has completed
- E.g., when calling accept, the calling thread is blocked until a request for a new client connection
- Problem: while a thread is blocked, it can't do anything else
- So, there is no way to support multiple simultaneous clients, and have the server be responsive, using a single thread
 - Or is there?



Nonblocking I/O

- Modern operating systems support nonblocking I/O
- In Unix/Linux, a file descriptor can be made nonblocking
- All operations that would normally block are guaranteed not to block if the filed descriptor is nonblocking
- If a blocking operation (accept, read, write) is invoked, but it can't be completed immediately:
 - Operation returns an error
 - errno is set to EWOULDBLOCK error code



Clicker quiz!

Clicker quiz omitted from public slides



Aside: errno, error codes

- When a C library or system call function fails, errno is set to an integer error code to indicate the reason for the failure
- Available using #include <errno.h>
- It's not actually a global variable (because that wouldn't work in a multithreaded program)
- Actual definition in the Linux C library (glibc):
 extern int *_errno_location (void) __THROW __attribute_const__;
 # define errno (*_errno_location ())
- __errno_location function returns a pointer to an integer variable allocated in thread-local storage
 - So, each thread has its own errno



An idea

Could we handle multiple client connections simultaneously as long as the server avoids doing any blocking I/O?



An idea

Could we handle multiple client connections simultaneously as long as the server avoids doing any blocking I/O?

Challenge: how do we know which file descriptors are ready to perform I/O?





Alternative approach for supporting multiple simultaneous client connections

Basic idea: server maintains sets of active file descriptors (mostly client connections, but also for file I/O)



Alternative approach for supporting multiple simultaneous client connections

Basic idea: server maintains sets of active file descriptors (mostly client connections, but also for file I/O)

Main server loop uses select or poll system call to check which file descriptors are *ready*, meaning that a read or write can be performed without blocking



Alternative approach for supporting multiple simultaneous client connections

Basic idea: server maintains sets of active file descriptors (mostly client connections, but also for file I/O)

Main server loop uses select or poll system call to check which file descriptors are *ready*, meaning that a read or write can be performed without blocking

Compared to using processes or threads for concurrency:

- Advantage: less overhead (CPU, memory) per client connection than processes or threads
- Disadvantage: higher code complexity



select system call

The select system call:

readfds, writefds, and exceptfds are sets of file descriptors

select waits until at least one file descriptor has become ready for reading or writing, or has an exceptional condition

- readfds, writefds, and/or exceptfds are modified to indicate the specific file descriptors that are ready
- timeout specifies maximum amount of time to wait, NULL means indefinitely



fd_set

An fd_set represents a set of file descriptors

Operations (where set is an fd_set variable):

- FD_ZERO(&set): make set empty
- FD_SET(fd, &set): add fd to set
- FD_CLR(fd, &set): remove fd from set
- FD_ISSET(fd, &set): true if fd is in set, false otherwise



I/O multiplexing main loop

Pseudo-code:

```
create server socket, add to active fd set
while (1) {
  wait for fd to become ready (select or poll)
  if server socket ready
    accept a connection, add it to set
  for fd in client connections
    if fd is ready for reading, read and update connection state
    if fs is ready for writing, write and update connection state
}
```



Updating connection state

The main difficulty of using I/O multiplexing is that communication with clients is *event-driven*



Updating connection state

The main difficulty of using I/O multiplexing is that communication with clients is *event-driven*

When data is read from the client, event-processing code must figure out what to do with it

• Data read might be a partial message



Updating connection state

The main difficulty of using I/O multiplexing is that communication with clients is *event-driven*

When data is read from the client, event-processing code must figure out what to do with it

• Data read might be a partial message

Similar issue when sending data to client: data might need to be sent in chunks

Maintaining and updating state of client connections is more complicated compared to code for process- or thread-based concurrency

• With these approaches, we can just use normal loops and control flow



Example: echo server

- Example: echoserv.c
- Protocol: read one line of text from client, send same line back, repeat until quit is received



Connection data structure

Per-connection data structure:

```
#define CONN READING
#define CONN_WRITING 1
#define CONN DONE
struct Connection {
  char in buf [BUFFER SIZE];
  char out buf [BUFFER SIZE];
  int in count, out pos, out count;
  int state;
};
in buf, in count: data received from client
out buf, out pos, out count: data to be sent to client
state: client state (CONN READING, CONN WRITING, or CONN DONE)
```




State machines

A synchronous network protocol can be modeled as a *state machine*

In a protocol implementation using threads or processes for concurrency, state is implicit

When implementing a protocol with I/O multiplexing, state must be explicit





Making a file descriptor nonblocking

Even when using select or poll to determine when file descriptors are ready, it is still a good idea to make them nonblocking

Avoids situations where an I/O operation might block

Making a file descriptor nonblocking:

```
void make_nonblocking(int fd) {
  int flags = fcntl(fd, F_GETFL, 0);
  if (flags < 0) {
    fatal("fcntl failed: could not get flags");
  }
  flags |= O_NONBLOCK;
  if (fcntl(fd, F_SETFL, flags) < 0) {
    fatal("fcntl failed: could not set flags");
  }
}</pre>
```



readfds and writefds

- Server has two fd_sets, readfds and writefds
- These specify the file descriptors that the server wants to check for being ready to read (readfds) or write (writefds)
- The server socket and the client file descriptors of all connections in the CONN_READING state are placed in readfds
- The client file descriptors of all connections in the CONN_WRITING state are placed in writefds
- Each call to select determines which file descriptors in readfds are ready for reading, and which file descriptors in writefds are ready for writing
 - If the server socket file descriptor is ready for reading, it means that a connection request has arrived (and a call to accept will not block)



Building readfds and writefds

```
// Code executed for each iteration of server main loop
// Place client socket fds in readfds and writefds as appropriate
for (int fd = 0; fd <= maxfd; fd++) {
  struct Connection *conn = client_conn[fd];
  if (conn) {
    if (conn->state == CONN READING) {
      FD_SET(fd, &readfds);
    } else if (conn->state == CONN WRITING) {
      FD SET(fd, &writefds);
// Server socket is always in readfds
FD_SET(serverfd, &readfds);
```



Determine which file descriptors are ready

```
int rc = select(maxfd + 1, &readfds, &writefds, NULL, NULL);
if (rc < 0) {
  fatal("select failed");
}</pre>
```

The maxfd variable keeps track of the maximum file descriptor value: select is more efficient when it checks fewer file descriptors for readiness



Accept a client connection

```
if (FD_ISSET(serverfd, &readfds)) {
  int clientfd = Accept(serverfd, NULL, NULL);
  make_nonblocking(clientfd);
  if (clientfd > maxfd) {
    maxfd = clientfd;
  }
  client_conn[clientfd] = create_client_conn();
}
```



Service client connections

```
for (int fd = 0; fd <= maxfd; fd++) {
  if (client_conn[fd] != NULL) {
    struct Connection *conn = client_conn[fd];
    if (FD ISSET(fd, &readfds)) {
      client do read(fd, conn);
    if (FD_ISSET(fd, &writefds)) {
      client do write(fd, conn);
    if (conn->state == CONN_DONE) {
      close(fd);
      free(conn);
      client_conn[fd] = NULL;
```



```
void client do read(int fd, struct Connection *conn) {
  int remaining = BUFFER SIZE - conn->in count - 1;
  ssize_t rc = read(fd, conn->in_buf + conn->in_count, remaining);
 if (rc < 0) {
   fatal("read failed");
 conn->in_count += rc;
 // process the data that was read
  ...40+ lines of code omitted...
```



```
void client do read(int fd, struct Connection *conn) {
  int remaining = BUFFER SIZE - conn->in count - 1;
  ssize_t rc = read(fd, conn->in_buf + conn->in_count, remaining);
 if (rc < 0) {
    fatal("read failed");
 conn->in_count += rc;
 // process the data that was read
  ...40+ lines of code omitted...
```

Code is fairly complicated because it must



```
void client do read(int fd, struct Connection *conn) {
  int remaining = BUFFER SIZE - conn->in count - 1;
  ssize_t rc = read(fd, conn->in_buf + conn->in_count, remaining);
  if (rc < 0) {
    fatal("read failed");
 conn->in_count += rc;
 // process the data that was read
  ...40+ lines of code omitted...
```

Code is fairly complicated because it must

Determine if a complete message was received



```
void client do read(int fd, struct Connection *conn) {
  int remaining = BUFFER SIZE - conn->in count - 1;
  ssize_t rc = read(fd, conn->in_buf + conn->in_count, remaining);
  if (rc < 0) {
    fatal("read failed");
  conn->in_count += rc;
 // process the data that was read
  ...40+ lines of code omitted...
```

Code is fairly complicated because it must

- Determine if a complete message was received
- If so, copy it to out_buf, deal with leftover data, update connection state



client_do_write

```
void client_do_write(int fd, struct Connection *conn) {
  int remaining = conn->out_count - conn->out_pos;
 ssize t rc = write(fd, conn->out buf + conn->out pos, (size t) remaining);
 if (rc < 0) {
   fatal("write failed");
 conn->out_pos += rc;
  if (conn->out_pos == conn->out_count) {
    conn->state = CONN READING;
```



client_do_write

```
void client_do_write(int fd, struct Connection *conn) {
  int remaining = conn->out_count - conn->out_pos;
  ssize t rc = write(fd, conn->out buf + conn->out pos, (size t) remaining);
 if (rc < 0) {
   fatal("write failed");
 conn->out_pos += rc;
  if (conn->out_pos == conn->out_count) {
    conn->state = CONN READING;
```

Fairly straightforward: just try to copy data from out_buf to the client socket



 The I/O multiplexing echo server implementation not terribly complex (a little over 200 lines of code)



- The I/O multiplexing echo server implementation not terribly complex (a little over 200 lines of code)
- **However**: the protocol was *very* simple



- The I/O multiplexing echo server implementation not terribly complex (a little over 200 lines of code)
- **However**: the protocol was *very* simple
 - and even so, client_do_read was quite complicated!



- The I/O multiplexing echo server implementation not terribly complex (a little over 200 lines of code)
- However: the protocol was very simple
 - and even so, client_do_read was quite complicated!
- Real protocols (e.g., HTTP) would be much more complicated to implement



- The I/O multiplexing echo server implementation not terribly complex (a little over 200 lines of code)
- However: the protocol was very simple
 - and even so, client_do_read was quite complicated!
- Real protocols (e.g., HTTP) would be much more complicated to implement
- ullet It would be nice if there were a way to get the benefits of I/O multiplexing, but write our code in a "threaded" style rather than an "event-driven" style



I/O multiplexing with coroutines



Coroutines

One way to reduce the complexity of I/O multiplexing is to implement communication with clients using *coroutines*

Coroutines are, essentially, a lightweight way of implementing threads

But with runtime cost closer to function call overhead

Each client connection is implemented as a coroutine

When a client file descriptor finds that a client fd is ready for reading or writing, it *yields* to the client coroutine

Client coroutine will do I/O, and then yield back to the main routine



Echo server implementation with coroutines

- echoserv_co.c is an echo server implementation using coroutines
- Similar number of lines of code as echoserv.c
- However, 30 lines of code are coroutine-aware versions of read and write
 - They check for EWOULDBLOCK and yield back to the main routine if a call to read or write would block
- Server main loop is very similar
- Actual protocol implementation is much simpler!



Echo server client coroutine

```
void chat_with_client(void) {
  struct Connection *conn = (struct Connection *) aco_get_arg();
 for (::) {
   // read a line
    conn->state = CONN_READING;
    co_readline(conn);
    // if line was "quit", we're done
    if (strcmp(conn->out_buf, "quit") == 0) {
      break:
    // echo line back to client
    conn->state = CONN WRITING;
    co_write_fully(conn->fd, conn->out_buf, strlen(conn->out_buf));
    co_write_fully(conn->fd, "\r\n", 2);
  aco exit();
```



Observations

- The chat_with_client function looks almost exactly like a thread start function
- The assignments to conn->state help the main routine know when to schedule the coroutine (based on the readiness of its file descriptor for reading or writing)
- The co_readline and co_write_fully functions are "coroutine-aware"
 I/O functions which yield back to the main routine if a call to read or write would block
- See complete code for details



Acknowledgements

Slides adapted from materials provided by David Hovemeyer.

